

Product Bulletin

VINYL DESTRUCT

PERMANENT ADHESIVE

A 1.5 mil cast vinyl film coated with 200-4934 permanent acrylic pressure sensitive adhesive on a 90# layflat liner. These films are designed to accept a variety of UV curable and solvent-based screen inks. Available in clear, white and silver colors.

Application	Inspection or property identification decals, non-removable guarantees or other uses where an emblem should not be removed or tampering made noticeable.
Thickness	Film – 1.5 mils. Adhesive – 0.8 to 1.0 mil. Liner – 6.7 mils. (Thickness variance +/- 10%)
Dimensional Stability	Good.
Temperature Ranges	Minimum application temperature is +45°F. Service temperature is -30°F to +200°F.
Expected Exterior Exposure	White & Silver - Up to 2 years. Clear – Limited.
Adhesion	Not applicable. Film tears when removed.
Water Resistance	Excellent.
Humidity Resistance	Excellent.
Storage Stability	2 years when stored under conditions of 70°F and 50% relative humidity.
Product Code	VDC-NTC-P/90# (Clear) VDW-NTC-P/90# (White) VDS-NTC-P/90# (Silver)



***Manufacturer of Pressure Sensitive Films,
Traffic Graffic Floor Advertising Films,
Custom Coatings and Printing Inks.***

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537
Web Site: www.generalformulations.com • e-mail: gfiinfo@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.