

Product Bulletin

SCREEN TAPE

A 2.0 mil metallized polyester film coated with 200-4986 permanent acrylic pressure sensitive adhesive on a 90# liner.

Applications	For use as an edge sealing tape for wooden or metal screen frames. Can also be used as a screen mesh patch.
Thickness	Film – 2.0 mils. Adhesive – 0.8 to 1.0 mil. Liner – 6.7 mils. (Thickness variance +/- 10%)
Dimensional Stability	Excellent.
Temperature Ranges	Minimum application temperature is +50°F. Service temperature is -40°F to +250°F.
Water Resistance	Limited.
Humidity Resistance	Good.
Storage Stability	2 years when stored at 70°F and 50% relative humidity.
Product Code	S2-TAPE



***Manufacturer of Pressure Sensitive Films,
Traffic Graffic Floor Advertising Films,
Custom Coatings and Printing Inks.***

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537
Web Site: www.generalformulations.com • e-mail: gfiinfo@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.