

Product Bulletin

FLEXIBLE GLOSS VINYL PERMANENT ADHESIVE

A 3.0 mil polished flexible calendered vinyl film coated with a 200-4981 permanent acrylic pressure sensitive adhesive on a 90# layflat liner. These films are designed to accept a variety of UV curable and solvent-based screen inks and could be topcoated for use with flexographic, offset and letterpress inks but must be tested prior to use.

Applications	This product is designed for permanent decals, nameplates, product markings and point of purchase decals.
Thickness	Film – 3.0 mils. Adhesive – 0.8 to 1.0 mil. Liner – 6.7 mils. (Thickness variance +/- 10%)
Dimensional Stability	Good.
Temperature Ranges	Minimum application temperature is +40°F. Service temperature range is -40°F to +200°F.
Expected Lifetime Exterior	Up to 2 years.
Adhesion	To stainless steel - 40 oz./in. PSTC-1 with 24 hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.
Water Resistance	Limited immersion resistance. Test for specific application.
Humidity Resistance	Good.
Storage Stability	2 year shelf life when stored at 70°F and 50% relative humidity.
Product Codes	VFGW-NTC-AP/90# – white, non-topcoated VFGB-NTC-AP/90# - black, non-topcoated VFGR-NTC-AP/90# - red, non-topcoated VFGY-NTC-AP/90# - yellow, non-topcoated



***Manufacturer of Pressure Sensitive Films,
Traffic Graffice Floor Advertising Films,
Custom Coatings and Printing Inks.***

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537
Web Site: www.generalformulations.com • e-mail: gfiinfo@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.