

# Product Bulletin

## FLEXIBLE GLOSS VINYL REMOVABLE ADHESIVE

A 3.0 mil polished flexible calendared vinyl film coated with a 200-4982 removable acrylic pressure sensitive adhesive on a 90# layflat liner. This product is designed to accept a variety of UV curable and solvent-based screen inks and solvent based digital printing inks. Test your ink and process on this product before production.

<b>Applications</b>	This product is designed for temporary decals, nameplates, product markings and point of purchase signage. Adhesive 200-4982 has low initial tack and designed for clean removability from glass windows. It may be applicable to other substrates such as metal, painted metal and certain plastic films. Test and approve the use of this product to your specific application before production.
<b>Thickness</b>	Film – 3.0 mils. Adhesive – 0.8 to 1.0 mil. Liner – 6.7 mils. (Thickness variance +/- 10%)
<b>Dimensional Stability</b>	Good.
<b>Temperature Ranges</b>	Minimum application temperature is +40°F. Service temperature range is -40°F to +200°F.
<b>Expected Exterior Exposure</b>	Removable up to 1 year under normal conditions.
<b>Adhesion</b>	To glass 5 to 15 oz. / in. To standard test panels 5 to 15 oz. / in. Tested according to PSTC-1 with 24-hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.
<b>Water Resistance</b>	Limited immersion resistance. Test for specific application.
<b>Humidity Resistance</b>	Good.
<b>Storage Stability</b>	1-year shelf life when stored at 70°F and 50% relative humidity.
<b>Product Codes</b>	VFGW-NTC-ARLT/90# – white, non-topcoated



***Manufacturer of Pressure Sensitive Films,  
Traffic Graffic Floor Advertising Films,  
Custom Coatings and Printing Inks.***

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537  
Web Site: [www.generalformulations.com](http://www.generalformulations.com) • e-mail: [gfiinfo@generalformulations.com](mailto:gfiinfo@generalformulations.com)

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.