

# Product Bulletin

## EXTENDED LIFE WHITE VINYL REMOVABLE ADHESIVE

A 3.4 mil specially formulated matte white flexible calendered vinyl film coated with 232-4727 removable acrylic pressure sensitive adhesive on a 90# layflat liner. The combination of vinyl and adhesive allows removability of the film from most common substrates for up to 2 years under normal exposure conditions. This film is designed to accept a variety of UV curable and solvent-based screen inks, and is available topcoated for use with flexographic, offset and letterpress inks but must be tested prior to use.

<b>Applications</b>	This product is recommended for signage, decals, nameplates, die-cut letters, point-of-purchase displays, billboards, motor and railway coaches. Markings for leased fleets and containers.	
<b>Thickness</b>	Film	3.4 mils.
	Adhesive	0.8 to 1.0 mil.
	Liner	6.7 mils.
	(Thickness variance +/- 10%)	
<b>Dimensional Stability</b>	Excellent.	
<b>Temperature Ranges</b>	Minimum application temperature	+20°F.
	Service temperature	-40°F to +180°F.
<b>Expected Life</b>	Removability - up to 2 years under normal exposure conditions. Durability - up to 5 years for a permanent application.	
<b>Adhesion</b>	To stainless steel - 32 oz./in. PSTC-101 with 24 hr. dwell at 70° F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.	
<b>Water Resistance</b>	Excellent.	
<b>Humidity Resistance</b>	Excellent.	
<b>Storage Stability</b>	1-year when stored at 70°F and 50% relative humidity.	
<b>Product Code</b>	VFWXL-NTC-R/90# (non-topcoated) VFWXL-TC-R/90# (topcoated)	



***Manufacturer of Pressure Sensitive Films,  
Traffic Graffice Floor Advertising Films,  
Custom Coatings and Printing Inks.***

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537  
Web Site: [www.generalformulations.com](http://www.generalformulations.com) • e-mail: [gfiinfo@generalformulations.com](mailto:gfiinfo@generalformulations.com)

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.