

# Product Bulletin

## FLEXIBLE WHITE VINYL PERMANENT ADHESIVE

A 3.2 mil matte flexible calendered white vinyl film coated with 200-4981 acrylic pressure sensitive permanent adhesive on a 90# layflat liner. These films are designed to accept a variety of UV curable and solvent-based screen inks but must be tested prior to use.

<b>Applications</b>	This product is designed for signage, decals, nameplates, die-cut letters and point-of-purchase displays.
<b>Thickness</b>	Film – 3.25 mils. Adhesive – 0.8 to 1.0 mil. Liner – 6.7 mils. (Thickness variance +/- 10%)
<b>Dimensional Stability</b>	Good.
<b>Temperature Ranges</b>	Minimum application temperature is +30°F. Service temperature is -40°F to +180°F.
<b>Expected Exterior Exposure</b>	Up to 3 years.
<b>Adhesion</b>	To stainless steel - 48 oz/in. PSTC-1 with 24 hr. dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.
<b>Water Resistance</b>	Limited immersion resistance. Test for specific application.
<b>Humidity Resistance</b>	Good.
<b>Storage Stability</b>	6 months shelf life when stored at 70°F and 50% relative humidity.
<b>Product Code</b>	<b>VFWM-NTC-AP/90#</b>



*Manufacturers of  
Pressure Sensitive Films*

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537  
Web Site: [www.generalformulations.com](http://www.generalformulations.com) • e-mail: [info@generalformulations.com](mailto:info@generalformulations.com)

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.