

# TECHNICAL DATA SHEET

## GF NFD 201HTAP

### 3.4 MIL PREMIUM MATTE WHITE FLEXIBLE CALENDERED VINYL FILM

NFD 201HTAP is a 3.4 mil premium matte white flexible calendered vinyl film which is coated with an aggressive permanent acrylic pressure sensitive adhesive and is laminated to a 90# lay flat liner. It is top coated with a cross-platform coating compatible with a wide array of narrow format production digital printing presses. The adhesive is designed to adhere to low energy surfaces. The 90# poly coated liner maintains lay flat characteristics in a variety of ambient conditions. GF NFD 201HTAP is available in 19" x 13" & 29.5" x 20.5" sheet sizes.

PRODUCT NAME	GF NFD 201HTAP
<b>FILM</b>	
Film Type	White Flex (Polymeric) Vinyl
Film Thickness (mils/μm)	3.4 / 86
Film Weight (gsm)	120
Gloss (60°)	≤ 20
Opacity (%)	93
<b>ADHESIVE</b>	
Adhesive Type	High-Tack Permanent
Adhesive Thickness (mils/μm)	0.8-1.0 / 20-26
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	4.0 / 18
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	4.0 / 18
<b>LINER</b>	
Liner Weight (# / gsm)	90 / 145
Liner Type	White PE Coated Kraft
Liner Thickness (mils / μm)	6.7 / 170
Release Force @ 300" / min (g/2")	20-30
<b>TOTAL CONSTRUCTION</b>	
Thickness (mils / microns)	11 / 274 (+/- 10%)
Weight (# per 3000ft <sup>2</sup> / gsm)	184 / 300
<b>PERFORMANCE GUIDANCE</b>	
Application Temperature	> +40°F
Service Temperature	-40°F to +180°F
Shelf Life	1 Year
Storage Temp / Rel. Humidity	70°F / 50% RH
Outdoor Durability	Up to 5 Years