

# Product Bulletin

## Concept® 114

### CLEAR MOUNTING FILM

Concept® 114 is a double-coated pressure sensitive 1.0 mil clear polyester film with the 200-4985 permanent adhesive on one side and 200-4982 removable adhesive on the other side. It is self wound on a white 76# paper liner. This product is designed for laminating thin flexible plastic films and papers commonly found in graphics for temporary application to glass. The permanent AP adhesive is exposed when the product is un-wound leaving the ARLT removable adhesive protected by the liner. This clear mounting film can be laminated by the cold laminating process without the addition of heat.

#### Applications

This clear mounting film is designed to mount digital prints, screen printed and other printed images to glass to produce a cleanly removable graphic. In all cases the substrates must be clean and free of dust, dirt and oil. Test your specific application before production.

#### Thickness

Film	1.0 mils.
Adhesive	0.8 to 1.0 mils each side.
Liner	4.5 mils.
(Thickness variance +/- 10%)	

#### Dimensional Stability

Good.

#### Temperature Ranges

Minimum application temperature	+30°F.
Surface must be clean and dry. Keep Concept® 114 warm as possible before application.	
Service temperature range	-40°F to +180°F.

#### Exterior Application

Removability of 200-4982 from standard window glass is up to 1 year under normal exposure conditions.

#### Adhesion

Removable Adhesive (ARLT)  
(AP adhesive laminated to 2-mil polyester film before adhesion testing)

To glass	5 to 15 oz. / in.
To standard test panels	5 to 15 oz. /in.

When tested according to PSTC-101 Method A procedures with 24-hr. dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary.  
Test thoroughly before production.

#### Storage Stability

One (1) year shelf life when stored at 70°F and 50% relative humidity.

#### Product Codes

114-38	38"x150'
114-51	51"x150'
114-54	54"x150'



**Manufacturer of Pressure Sensitive Films,  
Traffic Graffice Floor Advertising Films,  
Custom Coatings and Printing Inks.**

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537  
Web Site: [www.generalformulations.com](http://www.generalformulations.com) • e-mail: [gfiinfo@generalformulations.com](mailto:gfiinfo@generalformulations.com)

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.