

**TECHNICAL
DATA
SHEET**
**RV8-OPAQUE
SCREEN & OFFSET**
**8.0 MIL OPAQUE WHITE RIGID VINYL
NON-ADHESIVE PRODUCT**

A 8.0 mil matte white rigid vinyl print stock designed to produce two side window decals. This product offers high dyne levels, excellent opacity and layflat along with high tear strength. Designed for two-sided window decals requiring excellent blackout of the reverse graphics for either permanent or removable decals. Use with GF 113, 114, and 116 and to produce two-sided window decals. This product offers excellent adhesion to solvent screen; UV screen and UV offset inks designed for banners. However, printability and adhesion of your specific ink must be tested and approved before production. Available in sheets or rolls from 54 inch wide masters.

PRODUCT NAME	RV8-OPAQUE
FILM	
Film Type	Matte White Vinyl
Film Thickness (mils/ μ m)	8.0 mil / 203 μ m (+/- 10%)
Film Weight (gsm)	280
Gloss (60°)	\geq 20
Opacity (%)	\geq 99
ADHESIVE	
Adhesive Type	Not applicable
Adhesive Color	Not applicable
Adhesive Thickness (mils/ μ m)	Not applicable
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	Not applicable
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	Not applicable
LINER	
Liner Weight (#/gsm)	Not applicable
Liner Type	Not applicable
Liner Thickness (mils/ μ m)	Not applicable
Release Force @ 300" / min (g/2")	Not applicable
PERFORMANCE GUIDANCE	
Application Temperature	Not applicable
Service Temperature	-40 to 180 degrees F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 degrees F / 50%
Outdoor Durability	Limited. Test fully for any extended outdoor use.