

**TECHNICAL
DATA
SHEET**
**SR5-OL-1.5P/1.5
SCREEN & OFFSET**
**5.0 MIL SCRATCH RESISTANT TEXTURED MATTE VINYL
FLOOR LAMINATE | CLEAR PERMANENT ADHESIVE**

A 5.0 mil scratch resistant clear laminate with a textured matte finish. This laminating film is an inexpensive and durable alternative to polycarbonate film. It has a permanent solvent acrylic pressure sensitive adhesive formulated for exceptional clarity. Produced on a 1.5 mil polyester clear liner, the laminate has an extremely smooth adhesive coating. This product is designed to be paired with approved print films to create graphics for tile and carpet. It has been rated for slip resistance based on multiple testing methods.

PRODUCT NAME	SR5-OL-1.5P/1.5
FILM	
Film Type	Matte Clear Vinyl
Film Thickness (mils/ μ m)	5.0 mil / 127 μ m (+/- 10%)
Film Weight (gsm)	165
Gloss (60°)	10-25
Opacity (%)	Not applicable
ADHESIVE	
Adhesive Type	Permanent
Adhesive Color	Clear
Adhesive Thickness (mils/ μ m)	1.2-1.4 mil / 30-36 μ m
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	4.5 / 20
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	6.0 / 26
LINER	
Liner Weight (#/gsm)	Not applicable (+/- 10%)
Liner Type	Clear Polyester
Liner Thickness (mils/ μ m)	1.5 mil / 38 μ m
Release Force @ 300" / min (g/2")	25-50
PERFORMANCE GUIDANCE	
Application Temperature	\geq +40 degrees F
Service Temperature	-40 to 200 degrees F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 degrees F / 50%
Outdoor Durability	Indoor only