

TECHNICAL DATA SHEET

VFC3-OL-AP/53 SCREEN & OFFSET

3.0 MIL GLOSS CLEAR VINYL FLOOR LAMINATE
CLEAR PERMANENT ADHESIVE

A 3.0 mil gloss clear laminating vinyl designed for use as an economical slip-resistant protective laminate for Traffic Graffico® decals on tile or carpet. It has a permanent acrylic pressure sensitive adhesive formulated for exceptional clarity. This product is Intended as a laminate in the Traffic Graffico® line for high-traffic area floor graphics. The laminate can also be used for decals, table and counter top applications. It has been rated for slip resistance based on multiple testing methods.

PRODUCT NAME	VFC3-OL-AP/53
FILM	
Film Type	Gloss Clear Vinyl
Film Thickness (mils/μm)	3.0 mil / 76 μm (+/- 10%)
Film Weight (gsm)	100
Gloss (60°)	≥80
Opacity (%)	Not applicable
ADHESIVE	
Adhesive Type	Permanent
Adhesive Color	Clear
Adhesive Thickness (mils/μm)	0.8-1.1 mil / 20-28 μm
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	3.8 / 17
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	5.0 / 20
LINER	
Liner Weight (#/gsm)	53 / 86 (+/- 10%)
Liner Type	White Clay Coated Kraft
Liner Thickness (mils/μm)	3.5 mil / 89 μm
Release Force @ 300" / min (g/2")	10-40
PERFORMANCE GUIDANCE	
Application Temperature	≥ +40 degrees F
Service Temperature	-40 to 200 degrees F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 degrees F / 50%
Outdoor Durability	Indoor only
CERTIFICATIONS & RATINGS	
Slip Resistance	<ul style="list-style-type: none"> · UL 410 - Classified as Slip Resistant · AS HB198:2014 (AS/NZS 4586) - Dry PTV: 79, Wet PTV: 18 · ANSI A137.1/A326.3 - Dry DCOF: 0.96, Wet DCOF 0.24