

Product Bulletin

CVE-6.0-OL/53#

TRAFFIC GRAFFIC[®] OVERLAMINATE

A 6.0 mil clear flexible polished calendered vinyl film with a slight texture designed for use as the protective overlay for Traffic Graffico[®] decals. Adhesive 200-4981 is a permanent acrylic pressure sensitive adhesive formulated for exceptional clarity.

Applications

This product is intended for use as the overlaminating film to produce Traffic Graffico[®] floor decals. The adhesive is formulated to adhere to most common printing inks. However, specific formulations must be tested before use. Some inks may contain excessive flow additives that could reduce adhesion of this product. Test before production.

Slip Resistance

CVE-6.0-OL/53# is classified under UL 410 for floor graphics overlay applications.

Thickness

Film	6 mils.
Adhesive	.8 to 1.1 mils.
Liner	4 mils.
(Thickness variation +/- 10%)	

Temperature Ranges

Minimum application temperature	+40°F.
Service temperature	-40°F to +200°F.

Expected Exterior Exposure

This product is designed for interior applications. Exterior resistance has not been determined.

Durability

CVE-6.0 will function as a floor overlaminate for six (6) months under normal use.

Adhesion

To stainless steel	40 oz/in.
--------------------	-----------

Tested according to PSTC-1 with 24-hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.

Water Resistance

Excellent

Humidity Resistance

Excellent

Storage Stability

6 months shelf life when stored at 70°F and 50% relative humidity.

Product Code

CVE-6.0-OL/53#



***Manufacturer of Pressure Sensitive Films,
Traffic Graffico Floor Advertising Films,
Custom Coatings and Printing Inks.***

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537
Web Site: www.generalformulations.com • e-mail: gfiinfo@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.