

# Product Bulletin

## FLEXIBLE CLEAR VINYL LOW TACK REMOVABLE ADHESIVE

A 3.4 mil clear flexible polished vinyl film coated with 200-4982 low tack removable acrylic pressure sensitive adhesive on a 90# layflat liner. This product is designed to accept a variety of UV curable and solvent-based screen inks and is available topcoated for use with flexographic, offset and letterpress inks but must be tested prior to use.

<b>Applications</b>	This product is designed to produce temporary decals applied to windows.
<b>Thickness</b>	Film                    3.4 mils. Adhesive            0.8 to 1.0 mil. Liner                 6.7 mils. (Thickness variation +/- 10%)
<b>Dimensional Stability</b>	Good.
<b>Temperature Ranges</b>	Minimum application temperature is +40°F. Service temperature is -40°F to +200 F.
<b>Expected Exterior Exposure</b>	Clear vinyl film can yellow with exposure to UV radiation. Must be tested for specific usage. Removable up to 1 year under normal conditions.
<b>Adhesion</b>	To glass                                    3 - 9 oz/ in. To Standard Test Panels            5 -13oz/ in. Tested according to PSTC-1 with 24-hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.
<b>Water Resistance</b>	Limited immersion resistance. Test for specific application. If using the wet application method the product may fog when exposed to water. This condition will usually clear within 48 hours at normal temperature and humidity.
<b>Humidity Resistance</b>	Good. Under high humidity conditions product may fog. This condition will usually clear within 48 hours at normal temperature and humidity.
<b>Storage Stability</b>	6 months shelf life when stored at 70°F and 50% relative humidity.
<b>Product Code</b>	<b>VFC-NTC-ARLT/90#</b> (non-topcoated) <b>VFC-TC-ARLT/90#</b> (topcoated)



**Manufacturer of Pressure Sensitive Films,  
Traffic Graffice Floor Advertising Films,  
Custom Coatings and Printing Inks.**

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537  
Web Site: [www.generalformulations.com](http://www.generalformulations.com) • e-mail: [gfiinfo@generalformulations.com](mailto:gfiinfo@generalformulations.com)

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.