

TECHNICAL DATA SHEET

GF 226HTR WALLMARK™

6.0 MIL MATTE WHITE VINYL
CLEAR HIGH-TACK REMOVABLE ADHESIVE

GF 226HTR is a 6.0 mil matte white semi-rigid vinyl. GF 226HTR has a unique and innovative pressure sensitive adhesive that is specially formulated to be both high-tack and removable (HTR). The combination of vinyl and adhesive is designed to stick aggressively to most surfaces, but is specially formulated to remove cleanly for up to a year. It's also forgiving in the event you touch the adhesive to itself—it will separate cleanly and the adhesive stays anchored to the vinyl. The 90# layflat liner provides excellent stability for processing using solvent, latex and UV curable digital inks. common to wide format digital printing.

PRODUCT NAME	226HTR
FILM	
Film Type	White Polymeric Vinyl
Film Thickness (mils/μm)	6.0 / 152 (+/- 10%)
Film Weight (gsm)	218
Gloss (60°)	≤20
Opacity (%)	98
Tensile Strength (lbs/in ²)	MD ≥ 3000 / CD ≥ 3500
Elongation (%)	MD ≥ 130 / CD ≥ 200
Dimensional Stability (FTM 14)	MD ≤ 0.50 mm / CD ≤ 0.20 mm
ADHESIVE	
Adhesive Type	Solvent Acrylic
Adhesive Thickness (mils/μm)	0.9-1.1 / 23-28
Adhesive Color	Clear
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	1.0 / 4.4
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	1.4 / 6.1
LINER	
Liner Weight (#/gsm)	90 / 145
Liner Type	White 2-Sided PE-Coated Kraft
Liner Thickness (mils/μm)	6.7 / 170
Release Force @ 300" / min (g/2")	50-100
PERFORMANCE GUIDANCE	
Application Temperature	≥ +40 °F ❄️ (10° F cold weather tested for glass applications only)
Service Temperature	-40 °F to 180 °F
Shelf Life	up to 1 year
Storage Temp / Rel. Humidity	70 °F / 50%
Outdoor Durability	up to 5 years
Removability	up to 6 months
CERTIFICATIONS & RATINGS	
Flammability	ASTM E84 Class 1 or A (Rating Standard Test Method for Surface Burning characteristics of Building Materials)

**All values provided are typical averages intended for guidance only and should not be interpreted as product specifications or warranties.*

GF 226HTR | AUGUST 2026

309 S. UNION | SPARTA, MI 49345 | P:(616) 887-7387 | T:(800) 253-3664 | F:(616) 887-0537

WWW.GENERALFORMULATIONS.COM

TECHNICAL DATA SHEET

GF 226HTR - 6.0 MIL MATTE WHITE WALL VINYL CLEAR HIGH-TACK REMOVABLE ADHESIVE

PRODUCT SNAPSHOT	APPLICATIONS	INK TYPE
APPLICATION ○ WET APPLY ● DRY APPLY ○ LAMINATING ○ MOUNTING ● DIE CUTTABLE ○ HOT STAMP ○ THERMAL DIE ● FLATBED CUTTABLE	● POP/RETAIL ● WALL ○ WRAP ● WINDOW ○ FLOOR ○ TRANSLUCENT ● GENERAL SIGNAGE ● INDOOR ● OUTDOOR (SHORT TERM) ❄️ OUTDOOR (COLD TEMPS) This product has been tested for glass applications only at temperatures as low as 10° F. Laminating is recommended for films less than 6 mil thick to improve handling and ease of application. For best results at these low temperatures, the film must be applied dry.	● SOLVENT ● ECO-SOLVENT ● LATEX ● UV CURABLE ● SCREEN ● OFFSET (UV CURABLE) ○ OFFSET (CONVENTIONAL)
SUBSTRATES/SURFACES ● SMOOTH PAINTED DRYWALL ● GLASS		

FAQS	
Can I use GF 226HTR on other surfaces?	GF 226HTR is ideal for wall murals, decals, and graphics on most types of smooth painted interior walls, including flat, semi-gloss, and gloss paint finishes. The adhesive is also suitable for glass, tile, OEM-painted metal, sealed concrete, and most low-surface-energy substrates. When dry applied, GF 226HTR may be installed on glass at temperatures as low as 10°F (-12°C). Due to the variability of substrates and finishes, it is recommended to test for adhesive compatibility prior to installation.
Can I print edge-to-edge with 226HTR?	Yes! A great improvement with this product over the traditional GF 226 WallMark™ is that the adhesive will hold with minimal shrinkage for full bleed graphics without the need for an unprinted border.
When paneling larger jobs, do I use overlaps or butt-seams with this product?	Installation methods vary by both installer and project, but we consider either method to be acceptable, and the thickness and rigidity of GF 226 WallMark® HTR makes it easy to align panels. Butt seams are preferred, and you can expect minimal shrink with interior applications. As a benefit of the HTR product, the adhesive allows for minimal overlap as the High Tack adhesive bonds aggressively to the textured face of the vinyl. If overlapping, we recommend at least ½" to 1" for overlapping panels.