

**TECHNICAL  
DATA  
SHEET**
**GF 247 PRINT-N-LAM™**
**3.0 MIL GLOSS CLEAR UV VINYL  
CLEAR PERMANENT ADHESIVE**

GF 247 Print-n-Lam™ is a 3.0 mil Gloss Clear UV Polymeric Vinyl with clear permanent adhesive on a 90# layflat liner. GF 247 is designed to accept a variety of solvent, latex and UV curable inks common to wide format digital printing systems. It is specifically engineered for use in general signage, windows, and decal applications. GF 247 is ideal for printing or flat laminating.

<b>PRODUCT NAME</b>	<b>247</b>
<b>FILM</b>	
Film Type	Clear Polymeric Vinyl
Film Thickness (mils/μm)	3.0 / 76 (+/- 10%)
Film Weight (gsm)	100
Gloss (60°)	≥70
Opacity (%)	N/A
Tensile Strength (psi)	MD ≥ 3500 / CD ≥ 3500
Elongation (%)	MD ≥ 180 / CD ≥ 200
Dimensional Stability (FTM 14)	MD ≤ 2.00 mm / CD ≤ 1.00 mm
<b>ADHESIVE</b>	
Adhesive Type	Emulsion Acrylic
Adhesive Thickness (mils/μm)	0.8-1.1 / 20-28
Adhesive Color	Clear
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 15 min	3.2 / 14
Peel Strength on Stainless Steel (lbs/in) / (N/25mm) 24 hrs	5.0 / 22
<b>LINER</b>	
Liner Weight (#/gsm)	90 / 145
Liner Type	White 2-sided PE-Coated Kraft
Liner Thickness (mils/μm)	6.7 / 170
Release Force @ 300" / min (g/2")	17
<b>PERFORMANCE GUIDANCE</b>	
Application Temperature	≥ +40 °F
Service Temperature	-40 °F to 180 °F
Shelf Life	1 year
Storage Temp / Rel. Humidity	70 °F / 50%
Outdoor Durability	7 years

# TECHNICAL DATA SHEET

## GF 247 - 3.0 MIL GLOSS CLEAR UV VINYL CLEAR PERMANENT ADHESIVE

PRODUCT SNAPSHOT	APPLICATIONS	INK TYPE
<p><b>APPLICATION</b></p> <ul style="list-style-type: none"> <li><input type="radio"/> WET APPLY</li> <li><input checked="" type="radio"/> DRY APPLY</li> <li><input checked="" type="radio"/> LAMINATING</li> <li><input type="radio"/> MOUNTING</li> <li><input checked="" type="radio"/> DIE CUTTABLE</li> <li><input type="radio"/> HOT STAMP</li> <li><input type="radio"/> THERMAL DIE</li> <li><input checked="" type="radio"/> FLATBED CUTTABLE</li> </ul>	<ul style="list-style-type: none"> <li><input checked="" type="radio"/> POP/RETAIL</li> <li><input type="radio"/> WALL</li> <li><input type="radio"/> WRAP (FLAT)</li> <li><input checked="" type="radio"/> WINDOW</li> <li><input type="radio"/> FLOOR</li> <li><input type="radio"/> TRANSLUCENT</li> <li><input type="radio"/> FLEET (AS A FLAT LAMINATE)</li> <li><input checked="" type="radio"/> GENERAL SIGNAGE (FOR PRINT OR FLAT LAMINATE)</li> <li><input checked="" type="radio"/> OUTDOOR</li> </ul>	<ul style="list-style-type: none"> <li><input checked="" type="radio"/> SOLVENT</li> <li><input checked="" type="radio"/> ECO-SOLVENT</li> <li><input checked="" type="radio"/> LATEX</li> <li><input checked="" type="radio"/> UV CURABLE</li> <li><input type="radio"/> SCREEN</li> <li><input checked="" type="radio"/> OFFSET (UV CURABLE)</li> <li><input type="radio"/> OFFSET (CONVENTIONAL)</li> </ul>
<p><b>SUBSTRATES</b></p> <ul style="list-style-type: none"> <li><input checked="" type="radio"/> OEM PAINTED METAL</li> <li><input checked="" type="radio"/> PAINTED ALUMINUM</li> <li><input checked="" type="radio"/> STAINLESS STEEL</li> <li><input type="radio"/> FIBERGLAS</li> <li><input checked="" type="radio"/> ACRYLIC</li> </ul>		

### FAQS

Can I use GF 247 Print-n-Lam™ as a laminate?	Yes. GF 247 works equally well as a laminating film and can be paired with GF 333 AutoMark™ DRIFT™ PW for flat signage.
Can I wet apply GF 247 Print-n-Lam™?	It is possible, but since GF 248 is a water-based adhesive, there is the potential for temporary cloudiness when using commercial application fluids to apply this vinyl. The key is that the fluids needs to be queegeed out as thoroughly as possible. What little moisture & foginess that remains should then evaporate and dissipate in 24-48 hrs.
What applications are GF 247 Print-n-Lam™ good for?	For flat or general signage, commerical applications, P.O.P and permanent windows.